

Freezeproof IOWA® Yard Hydrant

These hydrants are intended for year round irrigation purposes and for filling field spray equipment, cleaning tools and equipment, lawn and garden care, watering livestock – immediate water flow even in sub-zero conditions.

Specifications:

Model No: Y34

Female Inlet: ¾" BSP

Casing: 1" Galvanized Steel Pipe

Operating Rod: ⅝" Galvanized Steel Pipe

Drain Hole: Tapped - ⅛" BSP

Removable Nozzle: ¾" Brass Male Hose Nozzle

Features:

- **Adjustable Link** - Provides easy and positive adjustment of the lever lock tension.
- **Rod Guide** - Eliminates side pull on rod, reduces wear on packing, packing nut & stem.
- **Flow Finder and Lock** - A simple cam that can be set to automatically obtain the same flow each time or lock against accidental opening.
- **Long Life Packing** - Graphite packing for lubricity and long life.
- **One Piece Variable Flow Plunger** - Large cushion type seal for longer life - is not easily damaged and assures shut-off even when foreign particles are present. Automatic drain feature - plunger opens drain to prevent freezing - closes at any flow to prevent wasting water.
- **Maintenance & Repair** - The IOWA® hydrant has been manufactured in the U.S. since 1929, and although many improvements have been made through the years, all parts are interchangeable. All repairs can be made from the top of unit without removing the hydrant from the ground.
- **Maximum Working Pressure:** 125 p.s.i.
- **Maximum Temperature:** 49°C (120° F)

DIMENSIONS ARE SHOWN IN IMPERIAL AS
HYDRANT MANUFACTURED IN USA

